



THE **P3** FREESTANDING PELLET STOVE

## THE **P3** FREESTANDING PELLET STOVE

Specifications	P3
Heat Output*	30,000 btu
Heating Area	1,200 ft <sup>2</sup>
Efficiency*	75%
Glass Size	130 in <sup>2</sup>
EPA Emissions	1.6 g/hr
Hopper Capacity	55 lbs
Variable Fan Speed	130 CFM

 $^{\ast}$  Efficiency, emissions and area heated will vary according to fuel type, venting, and location

## Clearance to Combustibles

Min. distance to the sides of the unit	8"
Min. distance behind the unit	4"
Min. distance from the base of the unit	48''
Min. distance from corner to wall	3"
Please see owner's manual for more information	

P3 Features
European designed cast iron accents
LED digital controls
Large glass size (130 in <sup>2</sup> )
Large ash pan
Included hearth pad
400 watt ignitor standard
Tri-mode thermostat design
Heavy duty welded heat exchanger
Service indicator
Compact design
Large hopper capacity
Available in three color variations
Hopper lid safety switch
Formed steel fluted liner



NEW "Comfort Level" System with Internal Thermostat



European designed cast iron accents



Large 55 lbs Capacity Pellet Hopper



Heavy Duty Welded Heat Exchanger



Optional Enameled Panels in Racing Red & Classic Ivory



Manufactured by Sherwood Industries Ltd Victoria, British Columbia, Canada info@enviro.com • enviro.com Printed in Canada, June 2014