# Dimplex®

## Opti-myst® Pro 1000
## Built-in Electric Firebox

GBF1000-PRO

**Impressive flames, completely customizable and versatile.**

Easily turn fireplace design concepts into reality with the Opti-myst Pro 1000 Built-in Electric Firebox.  Install as a single-sided unit, or remove the included backer panel and convert to a see-through design that opens the view between rooms.  The discrete heater completes the functionality and ensures perfect comfort in addition to the dazzling Opti-myst flame and smoke effect.

opti-myst®

# Opti-myst® Pro 1000
## Built-in Electric Firebox

**GBF1000-PRO**

Shown with backer panel removed, optional glass pane (GBF1000-GLASS), and included front glass kit (FG1000) installed.

31-3/4"
80.5 cm

**Customizable Flame**
Shown with slot inserts for a contemporary ribbon of flame.

46-5/8"
118.4 cm

16-1/4"
41.2 cm

**Customizable Flame**
Shown with spacer inserts for a more organic flame.

Optional Pro 1000 Log Kit (CDFILOG-KIT)

120 Volts | 1,460 Watts | 4,981 BTU

Optional Media Kits

CDFI1000-BLKRCK

CDFI1000-RVRCK

CDFI1000-DWSKIT

## Features

**Opti-myst® Flame Effect**
Revolutionary ultrasonic technology produces a fine mist to create the illusion of flames and smoke.

**Customizable Flame Width**
Includes spacers and slots for customizable flame width and pattern.

**Single or Double-sided**
Includes removable hi-gloss/reflective backer panel for easy conversion.

**Adjustable Flame Intensity**
Control the desired volume of flame.

**Supplemental Heat**
Includes an effective fan-forced heater to warm up to 400 sq. ft.; Heater heats one side, even with backer panel removed.

**Continuous Water Supply**
Optional plumbed water supply kit (CDFIPLUMB-KIT) provides continuous operation without refilling water tanks.

**Media Options**
Includes media tray that can be customized with any media (not included). Optional inner glow logs also available.

**Crackling Sound Effects**
Enjoy a more complete sensory experience with the sound of natural wood fire.

**Frame, Wire and Finish**
Basic installation requires fewer tradespeople, no gas lines, venting or chimney.

**Zero Emissions**
The most sustainable fireplace option; no emissions and 100% efficient.

**Energy Efficient**
Uses low-energy LED lights for low-cost operation.

**Sight and Sound Remote**
Control the flames, heater and sound at the touch of a button.

| Model # | Description | Lbs/Kg | UPC | Wty. | Carton Dimensions (WxHxD) | | Cube | |
|---|---|---|---|---|---|---|---|---|
| | | | | | inches | cm | Ft³ | M³ |
| Package consists of three cartons including (1) Pro 1000 Built-in Firebox, (1) Pro 1000 Cassette and (1) Front Glass Kit. | | | | | | | | |
| CDFI-BX1000 | Opti-myst® Pro 1000 Built-in Firebox | 37 / 81.4 | 781052 110618 | 2 yr. | 48-1/2 x 37 x 18-1/8 | 123.0 x 94.0 x 46.0 | 18.8 | 0.53 |
| CDFI1000-PRO | Opti-myst® Pro 1000 Cassette | 35 / 15.9 | 781052 112612 | 2 yr. | 44-1/2 x 13-3/8 x 18-1/8 | 113.0 x 34.0 x 46.0 | 6.2 | 0.18 |
| FG1000 | Front Glass Kit | 19.6 / 8.9 | 781052 118379 | 1 yr. | 50-5/8 x 20-7/8 x 5-1/8 | 128.5 x 53.0 x 13.0 | 2.9 | 0.08 |
| CDFILOG-KIT | Pro 1000 Log Kit (2 log sets) | 28 / 12.7 | 781052 104754 | 1 yr. | 23-1/2 x 17-3/4 x 22 | 60.0 x 45.1 x 55.9 | 5.3 | 0.15 |
| CDFI1000-BLKRCK | Black Rock Media | 24.2 / 11 | 781052 121065 | 1 yr. | (2) 14 x 3-1/4x 6-1/4 | (2) 6.34 x 1.44 x 2.82 | 0.16 | 0.00 |
| CDFI1000-RVRCK | River Rock Media | 23 / 10.4 | 781052 121072 | 1 yr. | (2) 14 x 3-1/4 x 6-1/4 | (2) 6.34 x 1.44 x 2.82 | 0.16 | 0.00 |
| CDFI1000-DWSKIT | Driftwood Media | 1.76 / .79 | 781052 121027 | 1 yr. | 25-1/8 x 5-3/8 x 5-5/8 | 62.7 x 13.7 x 14.3 | 043 | 0.01 |
| GBF1000-GLASS | Rear Glass Pane | 20.9 / 9.5 | 781052 116979 | 1 yr. | 50-5/8 x 21-5/8 x 4-7/8 | 128.5 x 55.0 x 12.5 | 2.9 | 0.08 |
| CDFIPLUMB-KIT | Plumb Kit | 0.7 / .32 | 781052 103221 | 1 yr. | 15-1/2 x 3-1/2 x 6-1/2 | 39.4 x 8.9 x 16.5 | 0.2 | 0.01 |

SE-183-010-071019

# Opti-myst® Pro 1000
## Built-in Electric Firebox

# GBF1000-PRO

## Product Dimensions:

FRONT

46-5/8"
118.4 cm

44-7/8"
114.0 cm

31-3/4"
80.5 cm

17-1/2"
44.4 cm

9-1/2"
24.0 cm

40-7/8"
103.8 cm

SIDE

14-3/4"
37.3 cm
MIN.
INSTALLATION
DEPTH

15-1/2"
39.3 cm

16-1/4"
41.2 cm

REAR

Flange

Back
Panel

Wire
Routing

Plumbing
Routing

## Framing Dimensions:

Minimum installation depth
14-3/4"
37.3 cm

32-3/8"
82.0 cm

45-1/4"
115.2 cm

**Bluetooth Receiver**
Must be connected for operation.
Can be recessed inside the wall
or installed for remote control
accessibility.

FRONT GLASS KIT - FG1000

40-5/8" (103.0 cm)

14-1/2"
(36.8 cm)

Depth with hinge - 1-5/8" (4.1 cm)

OPTIONAL REAR GLASS PANE - GBF1000-GLASS

40-5/8" (103.0 cm)

15-1/4"
(38.8 cm)

Depth with hinge - 1-5/8" (4.1 cm)

Remote
Control